


Name: Dylan Rodriguez
Date: 1-10-10
Track: Rev Race way

Track Conditions

Size: Open Med. Tight
 Traction: High Med. Low
 Surface: Smooth Med. Bumpy

Front Suspension



Kingpin ball spacer (Upper) _____ 1 mm
 Kingpin ball spacer (Lower) _____ 1 mm
 Upper arm spacer _____ 0 mm
 Toe angle _____ -3 °
 Rebound stop _____ 98% full mm
 Anti-roll bar _____ φ 2.3 mm

Lower arm mount (Kick up) 0 1

Lower arm plate (E0154A)

Upper arm position (E0148B, E0148C)

Lower arm spacer _____ 2mm

Front Shocks


Piston _____ 5 hole
 Oil # _____ 550
 Spring _____ 75-9.0
 Spring adjustment _____ mm



Steering Ackerman



Rear Suspension



Camber angle _____ 2.5 °
 Lower arm mount (Anti-squat) 0 1 (Toe angle) _____ 2.5 °

Rebound stop _____ 98% fullmm
 Anti-roll bar _____ φ 3.0mm
 Anti-squat (E0111C, E0111D)

Upright E0152
 E0173(Aluminium)

Wheelbase adjustment _____ 0 mm

Lower arm spacer _____ 0mm

Rear Shocks

Piston _____ 5 hole
 Oil # _____ 500
 Spring _____ 86-9.5
 Spring adjustment _____ mm



Wing Position



Engine Type O.S. 21
 Gasket _____ mm Reducer φ _____
 Plug OD 97t Fuel OD 30%
 Muffler O.S. 2050

Diff. Oil
 Front # 5 O-Ring _____ pcs. Other _____
 Center # 15 _____ pcs. Other _____
 Rear # 5 _____ pcs. Other _____

Tire
Front
 Type Hole Shot M3
 Foam _____
Rear
 Type Hole Shot M3
 Foam _____

Clutch
 Clutch shoes Aluminium _____
 Other _____
 Spring _____ mm
 Clutch bell / Spur gear /

Result
 Race time / Lap _____
 Best lap (1Lap) _____

Comments: This setup is with a BCE chassis and the ft hubs are 2mm extended buggy hubs ... ride height 36mm ft and 37 rr